



INLINE WATER FILTER INSTALLATION INSTRUCTIONS

REPLACING EXISTING EXTERNAL IN-LINE FILTERS

1. Locate isolation valve which will be located on the water supply line to the fridge. Turn it off and to depressurise the system draw a large glass of water from the water outlet at the fridge.

2. Have a bucket and towel ready as there will be a small spillage of water during this process

Remove the old filter by depressing the locking collar at each end of the filter with your thumb nail (or similar) and at the same time pull out the water supply line. Discard the old filter.

3. Cut the tube/hose neatly and straight, using a tube cutter or sharp knife to maintain it's circular structure and ensure no jagged edges.

4. Take the new filter, making sure the flow direction is correct and insert the inlet side only, the line will go in approx 5 – 10mm and you will feel it hit home.

5. **IMPORTANT** - Placing the filter in the bucket, turn on the water supply and allow about 5 litres of water to flow through the filter and into the bucket. This will remove any loose carbon fines. Turn off the water supply and connect the line that feeds into the fridge. Turn on the water supply and run approx 2 litres through the system.

6. Complete the Replacement Due sticker and place in a visible area inside the fridge door.



Use your finger or a sharp edged object to hold down the collar. This will allow the hose to easily slide out.



If your external filter currently has threaded fittings (plastic or brass) please note the following instructions:

1. Unscrew your fitting and remove hose from old filter.

2. Cut the tube/hose neatly, using a sharp knife to maintain it's circular structure and ensure no jagged edges.

3. Take the new filter, making sure the flow direction is correct and insert the inlet side only, the line will go in approx 5 – 10mm and you will feel it hit home.

4. **IMPORTANT** - Placing the filter in the bucket, turn on the water supply and allow about 5 litres of water to flow through the filter and into the bucket. This will remove any loose carbon fines. Turn off the water supply and connect the line that feeds into the fridge. Turn on the water supply and run approx 2 litres through the system.

5. Complete the Replacement Due sticker and place in a visible area inside the fridge door.

RESET LIGHT INSTRUCTIONS

NOTE: The fridge filter light indicator changes to every 6 months to indicate that you should change the water filter. If there is any interruption to the power of the fridge, the timer may reset for a further 6 months. Follow the instructions in your fridge manual to reset your fridge filter light upon installing your new filter. In the instance power is lost to the fridge, we highly recommend completing the Replacement Due sticker to keep an accurate record of replacement dates.